

Suitable for item codes: 687370C, 687370W, 687371C, 687371W, 687372C, 687372W, 687373C, 687373W, 687391C, 687392C, 687393C, 687394C

## Installation Instructions

Before installing your Grab Rail, please read through and consider instructions thoroughly.

### POINTS TO CONSIDER

**Cavity walls** - Please ensure the grab rail fixing points are secured to the wall's solid framing structure to ensure adequate mounting strength of the rail. To achieve this, you may be required to positioning the rail at an angle depending on the width between each wall stud and the length of rail you have selected.

**Solid walls** - If you need to install rail onto a solid (i.e. brick) wall, appropriate drilling equipment and additional wall plugs will need to be purchased to ensure rail strength.

**Please note:** It is required that Caroma Grab Rails are mounted to a secure and strong surface. Caroma will not accept responsibility for damage caused by incorrect installation or poor wall strength.

- III. Drill a hole at each of your marks with the specified drill bit (some wall surfaces may require specific drill sizes or additional fixing plugs - not included).
- IV. Re-position grab rail against surface while lining up drilled holes with holes in fixing plate. Attach rail using appropriate screws and tighten to ensure grab rail is strong and secure.
- V. Slide each cover plate back into position over the flange.
- VI. Align the dimples on the outside of cover plate to the raised edges of the flange. Push cover plate back firmly and rotate to lock.

**\*NZ4121 Compliance: Refer to the latest standard to ensure installation meets the requirements.**



**GWA**

Bathrooms & Kitchens

Caroma Industries Limited  
ABN 35 000 189 499  
1 Melito Court, Prestons NSW 2170  
National Customer Call Centre  
**13 14 16**  
**caroma.com.au**



New Zealand  
National Customer Call Centre  
**09 279 2700**  
**caroma.co.nz**

### INSTALLATION INSTRUCTIONS

- I. Pull back the cover plates to expose the fixing plate with holes. Please take care to ensure you don't scratch the rail surface.
- II. Position grab rail in desired location against wall or fixing surface. Using a pencil, mark the hole locations through fixing plate holes where the fixing screws are to be drilled.

### GRAB RAIL RANGE - lengths available

